

## Overview

### Product information



**PBSH-M12B-05P-FF-SL7002-20030000611**

Field mounted, Shielded, Female, Straight, M12, Coding B, Screw connector, Cable  
External cable diameter 6.0~7.5mm

### Product advantages

- Sealing optimization, protection level up to IP67
- Meet the harsh environment
- Suitable for various occasions connection technology
- Compatible with the international and domestic same series products

### Product certification



**RoHS**

**REACH**



## Technical data

### Product drawing

### 3D model

□

### Environmental conditions

Ambient temperature	-40°C...105°C
IP class	IP67

### General parameters

Rated current	4A
	60V
Number of potentials	5
Insulation resistance	≥ 100 MΩ
Error-proof coding	B-Code

Overvoltage level	II
Pollution level	3
Connection method	Screw connection
Torque	0.4 Nm

#### Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

#### Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

#### Dimension

Assembled cable outer diameter	6.0-7.5mm
Assembled conductor cross section	0.25~0.52 mm <sup>2</sup>
	24~20 AWG

#### Accessories

##### Accessories

Sealing cap	CAP-M12-MP-8004
-------------	-----------------

#### Business data

Order number	20030000611
Packing unit	/

Minimum order quantity	100
Products weight (without packaging)	/