


## Overview

## Product information

**DS2.5/1P-11040000240**

Plug-in terminal blocks, connector method: Push-in connector, Rated voltage : 500 V, Rated current : 24 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, Width: 5.2 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

## Product advantages

- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ Plug-in pluggable wiring system, which can be quickly installed and disassembled to realize modularization of circuit connection.
- ☑ Mis-plug-proof structure design, with DS-PC to prevent misconnection.
- ☑ With orange snaps, the plug can be fixed on the base.
- ☑ The plug can be flexibly assembled according to requirements.
- ☑ Equipped with test holes for easy testing of the circuit.

## Product certification



## Technical data

## Product drawing

## 3D model

## UL Electrical parameters

Rated voltage	600V
Rated current	20A

## Wiring data

Conductor cross section flexible (ferrule without plastic sleeve)	0.14-2.5mm <sup>2</sup>
Conductor cross section flexible (ferrule with plastic sleeve)	0.14-2.5mm <sup>2</sup>

2 flexible conductors with a TWIN ferrule	0.5mm <sup>2</sup>
Strip length	10~12mm
Conductor cross section solid	0.14~4mm <sup>2</sup>
Conductor cross section flexible	0.14~2.5 mm <sup>2</sup>
Conductor cross section solid AWG	26~12

#### Environmental conditions

Ambient temperature (storage / transport)	-25°C~60°C
Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

#### IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	24A
Rated surge voltage	6KV

#### Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

#### Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

#### Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

#### Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

## Dimension

Height	29.3mm
NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	48.6mm
width	5.2mm

## Overview

Insulating material group	I
standard test	IEC60947-7-1
Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

## Accessories

### Marker

Top marker	ZB5 / ZS5
Side marker	ZSF5
Marker support	DTH5-25x5 / DTH5-25x12

### Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	DFBXX-5.2

End cover	D-DS2.5
Plug	DSP2.5-H
Coding star	DS-PC
Latching	DSR1.5 / DSR2.5

#### Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

#### Business data

Order number	11040000240
Packing unit	100
Minimum order quantity	100
Products weight (without packaging)	5.18