

Overview

Product information



DSP2.5-H-M-11040000283

Plug, Nominal operating voltage: 500 V, Rated current: 24 A, Mode of connection: In connection, Rated connection capacity: 0.2 mm²-2.5 mm², Color: gray, Mounting type: Push-in connection technology

Product advantages

- Plug;
- Push-in connection technology, Tool free operation, more convenient and fast;
- Used for Push-in Terminals Blocks;
- According to the need, it can be assembled by itself.

Product certification

Technical data

Product drawing

3D model

□

Overview

| | |
|---|------|
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |
| Number of positions | 1 |
| color | Gray |

Dimension

| | |
|--------|--------|
| width | 5.2mm |
| Height | 39.2mm |
| length | 16mm |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75% |
| Ambient temperature (storage / transport) | -25°C~60°C |

Environmental protection

| | |
|------------|---------------------------------|
| RoHS | No excessive harmful substances |
| REACH SVHC | Lead 7439-92-1 |

Accessories

Business data

| | |
|-------------------------------------|-------------|
| Order number | 11040000283 |
| Packing unit | 100 |
| Minimum order quantity | 100 |
| Products weight (without packaging) | 2.89 |