




# MANGAS TRANSPARENTES



Libre de  
halógeno



Retardante  
de fuego



Alta  
flexibilidad



Temperatura de  
encogimiento: 125° C

CODIGO	Ø DIÁ. INTERNO (PULG)	Ø DIÁ. INTERNO (MM)	Ø DIÁ. INTERNO (MM)	ESPESOR (MM)	TAMAÑO DE CABLE (AWG)	ROLLO (M)	COLORES
WOER.RSFR-H-8-CL	5/16"	ØD 8MM	ØD 4.00MM	0.60MM	2-6 AWG	100M	
WOER.RSFR-H-10-CL	3/8"	ØD 10MM	ØD 5.00MM	0.60MM	2/0-4 AWG	100M	
WOER.RSFR-H-12-CL	1/2"	ØD 12MM	ØD 6.00MM	0.60MM	4/0-2 AWG	100M	
WOER.RSFR-H-15-CL	5/8"	ØD 15MM	ØD 7.50MM	0.70MM	1/0-300 MCM	100M	
WOER.RSFR-H-16-CL	5/8"	ØD 16MM	ØD 8.00MM	0.70MM	1/0-350 MCM	100M	
WOER.RSFR-H-18-CL	3/4"	ØD 18MM	ØD 8.00MM	0.80MM	2/0-500 MCM	100M	
WOER.RSFR-H-20-CL	3/4"	ØD 20MM	ØD 10.00MM	0.80MM	3/0-500 MCM	100M	
WOER.RSFR-H-22-CL	3/4"	ØD 22MM	ØD 11.00MM	0.80MM	4/0-600 MCM	100M	
WOER.RSFR-H-25-CL	1"	ØD 25MM	ØD 12.50MM	0.90MM	250-600 MCM	50M	
WOER.RSFR-H-30-CL	1 1/4"	ØD 30MM	ØD 15.00MM	0.95MM	300-1000 MCM	50M	
WOER.RSFR-H-35-CL	1 1/4"	ØD 35MM	ØD 17.50MM	1.00MM		50M	
WOER.RSFR-H-40-CL	1 1/2"	ØD 40MM	ØD 20.00MM	1.00MM		50M	
WOER.RSFR-H-50-CL	2"	ØD 50MM	ØD 25.00MM	1.00MM		25M	