


FLP-25-T1-V/3

pluggable module, visual fault signalling, module locking


- three-pole high performance lightning current arrester, leakage current-free
- installation at the boundary of zones LPZ 0 and LPZ 1 or higher, mainly to main distribution boards
- for protection against impact of direct or indirect lightning strikes in wide range of applications - houses, office and industrial buildings
- coordination with SPD type 2 (SLP-275 V) even without surge separating inductors



Dimension drawing



Basic circuit diagram



Parameter / Type		FLP-25-T1-V/3
Type of SPD		T1
Mounting		DIN rail 35 mm
Nominal voltage	U_n	230 V AC
Maximum operating voltage	U_c	260,00 V AC
Nominal load current for "V" connection	I_L	125 A
Type of network		TN
Maximum overcurrent protection		250 A gL/gG
Maximum overcurrent protection for "V" connection		125 A gL/gG
Short-circuit current rating	I_{SCCR}	50,0 kA
Total discharge current (10/350 μ s)	$I_{Total(10/350)}$	75,00 kA
Lightning impulse current (10/350 μ s)	I_{imp}	25,00 kA
Voltage protection level	U_p	1,50 kV
Response time	t_a	100 ns
TOV 5 s L-N		335 V
TOV characteristic (TOV 5 s)		withstand
Cross-section of connected conductors solid (min)		2,50 mm ²
Cross-section of connected conductors solid (max)		50,00 mm ²
Cross-section of connected conductors stranded (min)		2,50 mm ²
Cross-section of connected conductors stranded (max)		35,00 mm ²
Fault indication		red indication field
Remote indication		no
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 80 °C
Humidity		5 - 95 %
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000381

Plug module	FLP-25-T1-V/0
Customs tariff number	85363090
EAN	8595090553007
Ordering number	A05300